



UTP3320TS-PSB-L2

Switch PoE 16 puertos Gigabit + 4 Uplink Gigabit Combo (RJ45/SFP)
280W 802.3af/at 6KV Manejable Layer2



Características

- Switch PoE, de 16 puertos Gigabit + 4 Uplink Gigabit + 4 SFP Combo.
- Cumple con IEEE 802.3/802.3u/802.3ab/802.3X/802.3af/at(PSE).
- 16 puertos 10/100/1000 Base-T PoE+ RJ45(Auto-MDI/MDI-X).
- 4 puertos 1000 Base-T y 4 puertos 1000 Base-X SFP (Combo).
- 1 puerto de gestión PoE.
- Consumo de energía PoE 280W (30W máx por canal / 280W máx total).
- Temperatura de trabajo: 0°C - 45°C.
- Instalación en rack/sobremesa/pared.
- Dimensiones y peso: 440x315x44mm / 5Kg.

Accesorios

SFP-1.25G-20KM
SFP-1.25G-20KM-I
SFP-1.25G-20KM-RX
SFP-1.25G-20KM-SC-I-RX
SFP-1.25G-20KM-SC-I-TX
SFP-1.25G-20KM-TX
SFP-1.25G-550M
SFP-T

<https://www.ibdglobal.com/shop/product/utp3320ts-psb-l2-switch-poe-16-puertos-gigabit-4-uplink-gigabit-combo-rj45-sfp-280w-802-3af-at-6kv-manejable-layer2-17395>