

DR-UTP-A82



IPC test	
IPC protocol	ONVIF, RTSP, RTP
Ethernet test	10M/100M/1G Ethernet link detection; Ethernet loop detection; DHCP client and server; Ethernet traffic detection, data link quality detection.
IPC test	Discovering the device, real-time video, camera configuration, PTZ test, discovering ONVIF device cross the network segment.
IPC image test	H265/H264 decoding, support 4K@30FPS, local zoom preview (at 8 levels).
Interface	Dual-port RJ45 Ethernet 1Gbps, support serial connection;
WI-FI test	
WIFI test	Support 2.4G and 5G frequency band, WIFI connection, WIFI list, WIFI information detection, delay detection, test of packet loss rate.
Spectrum test	Support 2.4G and 5G frequency band, spatial frequency band signal scanning and detection, and spatial noise (interference) signal detection.
Signal monitoring	Support 2.4G and 5G frequency band quick monitoring of signal change, refresh frequency: 1-10Hz.
Antenna type	External foldable dual antenna. Dual band Dipole omnidirectional antenna
POE test	
PD test	The tester receives the power. 802.3at; power supply voltage detection
PSE test	The tester supplies the power. 802.3at;25.5Wmax, PD actual power detection
Analog video test	
Video format	NTSC/PAL/HD-CVI3.0 standard /AHD3.0 standard /HD-TVI3.0 standard
Video signal	1Vpp
Video input / output	Video IN BNC input, Video OUT BNC output
Video digital zoom	Support the zoom at 8 levels

DR-UTP-A82

Video signal generator	Sending PAL/NTSC video test signal, sending CVI, AHD and TVI video test signal (720P/1080P).
HDMI signal test	
HDMI Input	Can receive 720P 25/30/50/60Fps, 1080P 25/30Fps input signals for display
HDMI Output	Can output various formats of test images(720P 25/30/50/60Fps, 1080P 25/30Fps)
12V power output	
Power output	12V/2A output Interface: Round, external diameter 4mm; Internal needle : 1.6mm
Audio test	
Audio test	1 x Audio signal input
Coaxial PTZ control test	
Communication interface	Video IN BNC interface
Communication protocol	CVI protocol (Dahua coax), AHD protocol (Pelco-c) and TVI protocol (Hikvision)
485 PTZ control test	
Communication interface	RS485
Communication protocol	More than 30 protocols, including Pelco-D/P, Samsung, Panasonic, Lilin and Yaan
Baud rate	150, 300, 600, 1,200, 2,400, 4,800, 9,600 and 19,200bps
LED lighting(flashlight)	
Head LED	2 x 35lm LED, wide angel
TDR cable test	
Cable test	Testing the length of network cable (4 pairs). Resolution: 0.1 meter; Accuracy: 1 meter. The maximum length of the measured cable is 130-200 meters (depending on the wire rod).
Power supply	
Charger	12V/1.5A 5.5mm round-plug power supply
Battery	Equipped with two battery compartments One special lithium battery pack can be placed in each battery compartment, with a single capacity of 18.5Wh. The combined working time is about 10 hours (it also can work with a single battery).
Charging	12V/1.5A charging, Power: 18W,max. Charging time: 3~4 hours.
Power saving	Can set the automatic switching of overtime and display the icon of battery level in real-time.

DR-UTP-A82

System parameters	
Display screen	7.0" TFT 1920*RGB*1200 (resolution), 16.7M(color), Backlight brightness adjustable
Operation method	Power button, Master control keyboard with 13 keys, Full-fit technology capacitive Multi- touch screen (input)
Operation settings	Chinese/English interface, user optional
Automatic standby	Disabled/5-60 minutes
Keyboard tone	Enabled/ Disabled
Working environment and specifications	
Working temperature	-10°C~+55°C
Working humidity	30%~90%
Outline dimension	236.5x133.4x45.4mm