

## IP Smart Sight - Active Deterrence Cameras

Provision-ISR SMART-SIGHT Series includes high performances AI CAMERAS, designed for specific purposes and applications. All the devices' components (from the sensor, to the optics, through the CPU and even the lighting) were especially selected to deliver the most accurate AI result for the required application.



# I4-340AD-MVF

## 40M IR 4MP ACTIVE DETERRENCE MOTORIZED LENS BULLET CAMERA

Active deterrence cameras are designed to detect unwanted visitors and deter them by activating visual and audio alerts. Equipped with a 2.8-12mm motorized lens, this 4MP Dome/Turret camera is designed for medium distance surveillance (up to 40m) in both indoor and outdoor scenarios. The camera offers outstanding DDA Analytics (Detect, Distinguish, Alert) which has the ability to perform object recognition. With a variety of detection rules and triggers, the I4-340AD-MVF camera will let unwanted visitors know that their presence is known and being monitored.

- SMART IP
- MOTORIZED VF
- 4MP Resolution
- IP66 Protection rating
- 3 Axis
- 40m IR IR View 0 Lux
- DC12V POE Power supply
- Built-in Speaker
- Audio IN
- SD card



### MAIN FEATURES

- 4MP 2592×1520 Resolution
- Active Deterrence
- 2.8-12mm Motorized Vari-Focal (94.2°-29.8°)
- 3D-DNR
- IP66
- DDA Analytics.
- Audio in + Built in speaker
- Red/Blue Strobe Light

### ANALYTICS

- General Analytics: Camera Tampering
- AI (Object Recognition): Humans, 2/4 wheels vehicles  
DDA Sterile Area  
DDA Line Crossing  
DDA Object Counting



## SPECIFICATIONS

Image Sensor	1/3" CMOS (16:9)
Effective Pixels	2592X1520
Electronic Shutter	1/25s ~ 1/100000s
Frame Rate	1-25/30FPS In Normal Mode. 1-50/60FPS in HFR Mode***
Day & Night	ICR
Min. Illumination	Day: 0.1lux / Night: 0.005lux (@F1.6, AGC On) 0lux with IR on
Audio compression	G.711A/G.711U
Communication	Two-way Audio
Image Settings	AWB, AGC Adjustable, Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
Image Enhancement	True WDR (120dB), BLC, HLC, ROI
Noise Reduction	3D-DNR
Image Orientation	Mirror/Flip
Privacy Zone	Yes
Motion Detection	Yes
Analytics	Object Detection (Sterile Area, Line Crossing), Camera Tampering
Video Compression	H.265+/H.264+/H.265/H.264/MJPEG
Resolution	4MP / 2K / 3MP / 2MP / 1MP / D1 / QVGA / CIF / QCIF
Multi-Stream	Master Stream: 4MP(2592x1520) / 2K (2560x1440) / 3MP / 2MP / 1MP Sub-Stream: 1MP / D1 / CIF / QCIF Third Stream: D1 / CIF / QCIF (1~30fps)
Bit rate	64Kbps ~ 7Mbps@H.265 / 64Kbps ~ 8Mbps@H.264
Encode Mode	VBR/CBR
Image Quality	Five levels under VBR; Free adjustment under CBR
IR Distance	40m (2 High Power IR LED) Red/Blue Strobe light
Lens (Field of View)	2.8-12mm MVF with Auto Focus (94.2°-29.8°)

\*Main Stream Only, \*\*Sub-Streams Only, \*\*\*1080p,no true-WDR

## SPECIFICATIONS

Iris	DC Iris
Lens Mount	Ø14 Mount
Protection Rate	Water Proof: IP66
Bracket	3-Axis Bracket
Dimensions	220.8x79.4x81.2mm
Weight (gross)	~650g
Network	RJ45 (+PoE)
Power	DC Socket
Analog Video Output	No
Audio Connectivity	Built-In speaker + Audio Input
SD Card	Event/Schedule based Main/Sub-Stream recording (Up to 256Gb)
Hard Reset Button	Yes
Alarm	Alarm in + Alarm Out
Remote Monitoring	IE Browsing, Ossia VMS Software, Provision Cam2 Mobile App
User Access	Supports simultaneous monitoring for up to 10 users with multi-stream real time transmission
Network Protocol	IPv4, IPv6, TCP, UDP, DHCP, NTP, DDNS, 802.1X, RTSP, Multicast, UPnP, Email, FTP, HTTPS, QoS, P2P
ONVIF	Yes
Ethernet	100Mbps
PoE	Yes
Power Supply	DC12V/~780mA / PoE/~7.4W
Work Environment	-30°C~60°C, 10%~90% Humidity
Junction Box	PR-JB12IP66 - PR-JB12IP64

## DIMENSIONS



## ACCESSORIES



PR-JB12IP66



PR-JB12IP64